



HEADERS & GLAZING SYSTEMS

—
RP Headers
DriFit™ Glazing System
Floating Header



DORMA RP HEADERS

DORMA RP Header tubes are made to house the RTS overhead concealed closers and a variety of other pivot options.

The popularity of concealed overhead closers has led DORMA to furnish fully fabricated headers for every door and sidelite configuration.

The design of the DORMA RP Header system allows for a glazing pocket to be snapped into the header tube to permit

a seamless transition to the sidelite glazing. The Dri-Fit gasket is used for quick and easy installation. Profiles are available for glass thicknesses of 3/8" (10 mm), 1/2" (12 mm), 5/8" (15 mm), and 3/4" (19 mm) tempered glass.

Headers are available in two profiles:

- 1-3/4" x 4-1/8" (44 mm x 105 mm)
- 1-3/4" x 4-1/2" (44 mm x 114 mm)

DORMA DRI-FIT™ SYSTEM

DORMA Dri-Fit™ simplifies glazing installation. The Dri-Fit gasket is used in sidelite rails, header tube glazing pockets, and u-channels.

Dri-Fit side rails are available to match all DRS mechanical profile heights and offer saddle sizes from 1/8" to 3/4" (3 mm to 19 mm) tall.

DORMA also offers the Dri-Fit U-Channel—a low profile u-channel ideal for glazing with minimal hardware. It can even be recessed in the ceiling and floor to completely eliminate visible hardware.

Five stock finishes are available. Non-stock finishes are available upon request with additional lead time. Extrusions come in stock lengths up to 144" (3658 mm) and 120" (3048 mm) for Brass & Bronze finishes.



DORMA FLOATING HEADER



The DORMA Floating Header allows all-glass entrances with transoms to be installed with overhead closers. The floating header connects to the

adjoining sidelite glass—providing a platform for installing overhead closers, magnetic locks, door stops, or walking beam pivots.

- Available in standard architectural metal finishes for single and double door applications, in widths of 4-1/8" or 4-1/2" (105 mm or 114 mm).

- Applications:
 - Office
 - Retail
 - Conference Rooms

DORMA Dri-Fit™ Glass Thickness Availability

Glass Thickness (fully tempered)	3-5/8" (92 mm) SQ Dri-Fit Rail	3-5/8" (92 mm) TP Dri-Fit Rail	4" (102 mm) SQ Dri-Fit Rail	6" (152 mm) SQ Dri-Fit Rail	10" (254 mm) SQ Dri-Fit Rail	1" x 1" (25mm x 25mm) Dri-Fit U-Channel	1" x 1-3/4" (25mm x 44mm) Dri-Fit U-Channel	1-1/4" x 1" (32mm x 25mm) Dri-Fit U-Channel	1-1/4" x 1-3/4" (32mm x 44mm) Dri-Fit U-Channel
3/8" (10 mm) or 1/2" (12 mm)	X	X	X	X	X	X	X		
5/8" (15 mm) or 3/4" (19 mm)	X			X				X	X

DORMA USA, Inc.
 Dorma Drive, Drawer AC
 Reamstown, PA 17567
 800-523-8483
 www.dorma.com